

ULTRA-LARGE SPLIT SPHERICAL ROLLER BEARINGS

ADVANCED SOLUTIONS FOR BOF AND CONVERTER TRUNNIONS





MADE WITH METTLE

BEARINGS FOR STEEL AND METALS MACHINERY

Massive loads. Intense heat. Extreme high speeds, ultra-low speeds, and everything in between. Staggering shock loads, misalignment, and contamination from mill scale and water vapor. From primary iron and steel making through rolling and forming mills, the operating conditions of the entire process are severe. The reliable, uninterrupted performance of rolling components is critical for accelerated production. For NSK, our product development and design is focused squarely on withstanding the manifold operating stresses of these applications with:

- increasing capacities for high loads and high speeds
- > advanced materials for durability, wear resistance and longer life
- > lubrication and seal technology for smooth and clean running

Our product solutions are designed to optimize the performance of machinery and equipment, to assure predictable reliability and to deliver total cost-efficiency.



ULTRA-LARGE SPLIT BEARINGS

NSK

Conventional bearing replacement for BOF's and Converters can be an exhaustive and critically time-consuming enterprise, requiring extensive dismantling of surrounding equipment and components in order to access inboard bearing installations. With NSK's split spherical bearing design, removing the bull gear and/or furnace tilt drive in order to gain access is eliminated, and actual bearing replacement is simplified. As result, maintenance time and costs are significantly reduced, as is the impact to productivity in subsequent processes.

And in this case convenience does not come at a cost or compromise.

NSK Ultra-Large Split Bearings are engineered to operate with stability at high temperatures, accommodating heavy loads, low speeds and oscillating motion with predictably reliable efficiency.

Split inner and outer rings

Split roller/cage assemblies


Split fastening ring with contact-type sealing surface


Fastening ring is also used as a seal sliding surface


PROVEN ADVANTAGES

- > Simplified, faster installation with split design
- Split bearings can be replaced without extensive dismantling, reducing maintenance time and costs
- Reduced downtime mitigates production loss in subsequent processes

BEARING DIMENSIONS AND OPERATING VALUES







1) clamp ring

2) clamp ring with tangential seal surface


	BEARING DIMENSIONS									BASIC LOAD RATINGS		
BASIC BEARING NO.	mm									kN		DESIGN
		D	В		b ₁	D ₁	D _u	r, (min)	r ₂ (min)	Dynamic	Static	
750SLPT1051	750	1 000	250	355		905	914	6.0	7.5	6 800	18 300	1
SL850-7	850	1 120	272	385		1 015	1 025	6.0	6.0	8 000	21 600	1
900SLPT1251	900	1 250	285	410		1 100	1 142	7.5	19.0	9 850	24 200	1
950SLPT1451	950	1 400	300	520	600	1 182	1 265	7.5	28.0	12 300	27 900	2
SL1120-3	1 120	1 580	320	633	698	1 400	1 445	9.5	30.0	13 200	32 000	2
1200SLPT1751	1 200	1 700	410	780	780	1 470	1 536	9.5	31.0	17 300	43 500	2*
1200SLPT1752		1 700	410	660	730	1 470	1 536	9.5	19.0	17 300	43 500	2
1320SLPT1851	1 320	1 850	530	815	814	1 600	1 670	12.0	31.0	22 500	63 500	2
1400SLPT1951	1 400	1 900	530	880	880	1 680	1 710	12.0	31.0	22 800	65 000	2*
1400SLPT1953		1 900	530	810	860	1 680	1 710	12.0	31.0	22 800	65 000	2*

Bearing designs indicated 2* differ slightly from illustration Additional bearing sizes are available. Please contact NSK for additional information.

DESIGNATION SYSTEM

Bore Diameter in mm	Bearing Type	NSK Design Number		
1200	SLPT	1751		





MAINTENANCE COST BENEFITS

- > Simplified and faster installation with split design
- Split bearings can be replaced without extensive dismantling, reducing maintenance time and costs
- Reduced downtime mitigates production loss in subsequent processes

Field Test: Comparison of bearing replacement time

Conventional solution: solid-type	100%		
Advanced solution: split spherical roller bearing	65%	Maintenan reduction	^{.ce} 35%

The bearing replacement period represents the actual result for bearings with bore diameter of 1200 mm to 1400 mm.



NSK AMERICAS

United States NSK Corporation Ann Arbor MI 1.888.446.5675

Canada NSK Canada Inc. Mississauga ON 1.888.603.7667

Mexico NSK Rodamientos Mexicana, S.A. de C.V. Silao Guanajuato MX 52.472.500.9500

Brazil NSK Brasil Ltda. Sao Paulo SP 55.11.3269.4700

Argentina NSK Argentina SRL Buenos Aires 54.11.4762.6556

Latin America NSK Latin America Inc. Miami FL 1.305.477.0605

Website: www.nskmetals.com

NSK Americas: www.nskamericas.com

NSK Global: www.nsk.com

Every care has been taken to ensure the accuracy of the data contained in this brochure, but no liability can be accepted for any loss or damage suffered through errors or omissions.

Printed in the USA ©NSK 2021. The contents of the publication are the copyright of the publishers.

